

	AL6XN												
	A superaustenitic stainless steel with outstanding resistance to chloride pitting,												
	crevice corrosion and stress corrosion cracking.												
	HEX NUT												
3/8-16	Х												
7/16-14	Х												
1/2-13	Х												
5/8-11	Х												
3/4-10	Х												
	HEX BOLTS												
	III ZX BO												
THREAD	3/8-16	7/16-14	1/2-13	5/8-11	3/4-10								
LENGTH													
1 3/4		Х											
2	Х			Х	Х								
3			Х	Х									
ALLOY	20												
Designed	d specifica	lly to with	stand sul	furic acid	. Its nickel	l, chromium,	molybdenu	ım					
						n resistance.							
		•											
	HEX NUT			FLAT WA	SHER								
1/2-13	X			1/2	X								
5/8-11	Х			5/8	Х								
3/4-10	Х			3/4	X								
-,													
	1	HEX BOLTS											
		HEX BO	LIS										
TUDEAR	1/2 12												
THREAD LENGTH	1/2-13	5/8-11	3/4-10										



1 1/4	Х					
1 1/2		X				
2	Х					
2 1/4		Х				
2 1/2		Х	Х			
3		Х	Х			
3 1/2		Х				
	THREA	DED RO	D			
SIZE	3 FT	6 FT				
3/8-16	Х					
1/2-13	Х					
5/8-11	Х	Х				
3/4-10	Х	X				
7 - 2						
					1	